# SPIVER S.r.I. Revision nr. 12 Dated 15/01/2016 Printed on 09/03/2016 Page n. 1/11

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CERALUX

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use decorative internal coating.

1.3. Details of the supplier of the safety data sheet

Name SPIVER S.r.I.

Full address Contrada Babbaurra SS 122
District and Country 93100 CALTANISSETTA (CL)

ITALY

Tel. +39 0934 577791 Fax +39 0934 588795

e-mail address of the competent person

responsible for the Safety Data Sheet info@spiver.it

1.4. Emergency telephone number

For urgent inquiries refer to +39 0934 577791

# **SECTION 2. Hazards identification.**

## 2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments. Hazard classification and indication:

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

EUH208 Contains:

5-Chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone

May produce an allergic reaction.

Precautionary statements:

# SPIVER S.r.I. Revision nr. 12 Dated 15/01/2016 Printed on 09/03/2016 Page n. 2/11

--

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

## 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
ETHANEDIOL		(01.).
CAS. 107-21-1	1 - 5	Acute Tox. 4 H302
EC. 203-473-3		
INDEX. 603-027-00-1		
5-Chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone		
CAS. 55965-84-9	0 - 0,0015	Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B H314, Skin Sens. 1 H317, Aquatic

EC. -INDEX. -

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures.**

## 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

Acute 1 H400 M=1, Aquatic

Chronic 1 H410

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

# 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

SPIVER S.r.I.	Revision nr. 12
	Dated 15/01/2016
CERALUX	Printed on 09/03/2016
	Page n. 3/11

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

## 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters.

# GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

## 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

SPIVER S.r.I.	Revision nr. 12
	Dated 15/01/2016
CERALUX	Printed on 09/03/2016
	Page n. 4/11

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

## 7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

## 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

# 8.1. Control parameters.

Regulatory References:

ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Veiledning om Administrative normer for forurensning i arbeidsatmosfære
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

ETHANEDIOL						
Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	52	20	104	40	SKIN.
VLEP	FRA	52	20	104	40	SKIN.
WEL	GRB	52	20	104	40	
TLV	ITA	52	20	104	40	SKIN.

		SPIVE	R S.r.I.				Revision nr. 12  Dated 15/01/2016
		CER/	ALUX				Printed on 09/03/2016
							Page n. 5/11
TLV	NOR		25			SKI	N
			25			SKI	N.
NDS	POL	15		20			
OEL	EU	52	20	104	40	SKI	N.
TLV-ACGIH				100 (C)			

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

# ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties.**

# 9.1. Information on basic physical and chemical properties.

Appearance liquid Colour transparent Odour **FLOREALE** Odour threshold. Not available. 8 - 10 Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. > 60 °C. Not available. **Evaporation Rate** Flammability of solids and gases Not available. Lower inflammability limit. Not available.

# SPIVER S.r.I. Revision nr. 12 Dated 15/01/2016 Printed on 09/03/2016 Page n. 6/11 Page n. 6/11

Upper inflammability limit.

Lower explosive limit.

Upper explosive limit.

Vapour pressure.

Vapour density

Relative density.

Not available.

Not available.

Not available.

Not available.

1,030 Kg/l

Solubility MISCIBLE IN WATER

Partition coefficient: n-octanol/water
Auto-ignition temperature.

Decomposition temperature.

Viscosity

Explosive properties

Oxidising properties

Not available.

Not available.

Not available.

Not available.

Not available.

9.2. Other information.

VOC (Directive 2004/42/EC): 2,85 % - 29,35 g/litre.

VOC (volatile carbon):

# SECTION 10. Stability and reactivity.

## 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL: can absorb atmospheric humidity up to twice its own weight. Decomposes at temperatures over 200°C/392°F.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL: risk of explosion on contact with: perchloric acid. Can react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with the air.

# 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL: avoid exposure to sources of heat and naked flames.

#### 10.5. Incompatible materials.

Information not available.

SPIVER S.r.I.	Revision nr. 12
	Dated 15/01/2016
CERALUX	Printed on 09/03/2016
	Page n. 7/11

#### 10.6. Hazardous decomposition products.

ETHANEDIOL: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, formaldehyde, carbon monoxide, hydrogen.

# **SECTION 11. Toxicological information.**

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains sensitizing substance/s and may cause allergic reactions.

ETHANEDIOL: following ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1,4 l/kg. The way of entry is inhalation and ingestion.

ETHANEDIOL LD50 (Oral).> 2000 mg/kg Rat LD50 (Dermal).9530 mg/kg Rabbit

# **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

# 12.1. Toxicity.

Information not available.

# 12.2. Persistence and degradability.

ETHANEDIOL

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

## 12.3. Bioaccumulative potential.

**ETHANEDIOL** 

Partition coefficient: n- -1,36

octanol/water.

12.4. Mobility in soil.

Information not available

## 12.5. Results of PBT and vPvB assessment.

SPIVER S.r.I.	Revision nr. 12  Dated 15/01/2016
CEDALIIV	Printed on 09/03/2016
CERALUX	Page n. 8/11
	<u> </u>
On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.	
12.6. Other adverse effects.	
Information not available.	
SECTION 13. Disposal considerations.	
13.1. Waste treatment methods.	
Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  Disposal must be performed through an authorised waste management firm, in compliance with national and local recontaminated PACKAGING	gulations.
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulatio	ns.
SECTION 14. Transport information.	
14.1. UN number.	
Not applicable.	
14.2. UN proper shipping name.	
Not applicable.	
14.3. Transport hazard class(es).	
Not applicable.	
AAA Baaliina aasaa	
14.4. Packing group.	
Not applicable.	
14.5. Environmental hazards.	
Not applicable.	
14.6. Special precautions for user.	
THE SPECIAL PROGRAMMENT TO LASE .	

	SPIVER S.r.I.	Revision nr. 12
	Of IVER O.I.I.	Dated 15/01/2016
	CERALUX	Printed on 09/03/2016
	CLINALUX	Page n. 9/11
		I
Not applicable.		
14.7. Transport in bulk according to	Annex II of MARPOL73/78 and the IBC Code.	
Information not relevant.		
SECTION 15. Regulatory	information.	
15.1 Safety health and environme	ntal regulations/legislation specific for the substance o	r miytura
13.1. Galety, fleathr and environme	mai regulations/legislation specific for the substance of	mixture.
Seveso category.	None.	
		4007/0000
Restrictions relating to the product or c	ontained substances pursuant to Annex XVII to EC Regulati	on 1907/2006.
None.		
Substances in Candidate List (Art. 59 F	<u>(EACH).</u>	
None.		
Substances subject to authorisarion (A	nnex XIV REACH).	
None.		
T to lie		
Substances subject to exportation repo	rting pursuant to (EC) Reg. 649/2012:	
None.		
Notice.		
Substances subject to the Rotterdam C	convention:	
None		
None.		
Substances subject to the Stockholm C	Convention:	
None.		
Healthcare controls.		
Information not available.		
VOC (Directive 2004/42/EC) :		
Decorative effect coatings.		
VOC given in g/litre of product in a		
ready-to-use condition:		
Limit value:	200,00 (2010)	
VOC of product :	29,35	

15.2. Chemical safety assessment.

# SPIVER S.r.I. Revision nr. 12 Dated 15/01/2016 Printed on 09/03/2016 Page n. 10/11 Page n. 10/11

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3 Acute toxicity, category 3

Acute Tox. 4 Acute toxicity, category 4

Skin Corr. 1B Skin corrosion, category 1B

Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H301 Toxic if swallowed.
H311 Toxic in contact with skin.

H331 Toxic if inhaled.H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

**H410** Very toxic to aquatic life with long lasting effects.

**EUH210** Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament

SPIVER S.r.I.	Revision nr. 12
	Dated 15/01/2016
CERALUX	Printed on 09/03/2016 Page n. 11/11

- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: